

# Package ‘MultiATSM’

November 5, 2025

**Type** Package

**Title** Multicountry Term Structure of Interest Rates Models

**Version** 1.5.1

**Date** 2025-11-05

**Description** Package for estimating, analyzing, and forecasting multi-country macro-finance affine term structure models (ATSMs). All setups build on the single-country unspanned macroeconomic risk framework from Joslin, Priebsch, and Singleton (2014, JF) <[doi:10.1111/jofi.12131](https://doi.org/10.1111/jofi.12131)>. Multicountry extensions by Jotikasthira, Le, and Lundblad (2015, JFE) <[doi:10.1016/j.jfineco.2014.09.004](https://doi.org/10.1016/j.jfineco.2014.09.004)>, Candellon and Moura (2023, EM) <[doi:10.1016/j.econmod.2023.106453](https://doi.org/10.1016/j.econmod.2023.106453)>, and Candellon and Moura (2024, JFEC) <[doi:10.1093/jfinec/nbae008](https://doi.org/10.1093/jfinec/nbae008)> are also available. The package also provides tools for bias correction as in Bauer Rudebusch and Wu (2012, JBES) <[doi:10.1080/07350015.2012.693855](https://doi.org/10.1080/07350015.2012.693855)>, bootstrap analysis, and several graphical/numerical outputs.

**License** GPL-2 | GPL-3

**Encoding** UTF-8

**RoxygenNote** 7.2.3

**Imports** cowplot, ggplot2, hablar, magic, pracma

**Suggests** readxl, testthat (>= 3.0.0), knitr, rmarkdown, bookdown, kableExtra, magrittr

**Depends** R (>= 4.3.0)

**VignetteBuilder** knitr

**URL** <https://github.com/rubensmoura87/MultiATSM>,  
<https://rubensmoura87.github.io/MultiATSM/>

**BugReports** <https://github.com/rubensmoura87/MultiATSM/issues>

**NeedsCompilation** no

**Author** Rubens Moura [aut, cre] (ORCID:  
<<https://orcid.org/0000-0001-8105-4729>>)

**Maintainer** Rubens Moura <[rubens.gtmoura@gmail.com](mailto:rubens.gtmoura@gmail.com)>

**Repository** CRAN

**Date/Publication** 2025-11-05 15:00:02 UTC

**Config/testthat/edition** 3

**LazyData** true

## Contents

|                                    |    |
|------------------------------------|----|
| autoplot . . . . .                 | 3  |
| autoplot.ATSMModelBoot . . . . .   | 3  |
| autoplot.ATSMNumOutputs . . . . .  | 4  |
| Bias_Correc_VAR . . . . .          | 4  |
| Bootstrap . . . . .                | 6  |
| BR_jps_out . . . . .               | 8  |
| DatabasePrep . . . . .             | 9  |
| DataForEstimation . . . . .        | 10 |
| DomMacro . . . . .                 | 12 |
| DomMacro_covid . . . . .           | 13 |
| FEVDandGFEVDgraphs . . . . .       | 14 |
| Fitgraphs . . . . .                | 15 |
| ForecastYields . . . . .           | 16 |
| GlobalMacro . . . . .              | 18 |
| GlobalMacro_covid . . . . .        | 19 |
| GVAR . . . . .                     | 19 |
| GVARFactors . . . . .              | 21 |
| InpForOutEx . . . . .              | 22 |
| InputsForOpt . . . . .             | 22 |
| InputsForOutputs . . . . .         | 26 |
| IRFandGIRFgraphs . . . . .         | 28 |
| JLL . . . . .                      | 29 |
| LabFac . . . . .                   | 30 |
| LoadData . . . . .                 | 31 |
| Load_Excel_Data . . . . .          | 32 |
| MultiATSM . . . . .                | 33 |
| MultiATSM_datasets . . . . .       | 33 |
| NumOutEx . . . . .                 | 34 |
| NumOutputs . . . . .               | 35 |
| Optimization . . . . .             | 36 |
| Out_Example . . . . .              | 38 |
| ParaSetEx . . . . .                | 39 |
| pca_weights_one_country . . . . .  | 39 |
| plot.ATSMModelForecast . . . . .   | 40 |
| print.ATSMModelInputs . . . . .    | 40 |
| RiskFacFull . . . . .              | 41 |
| RiskFactorsGraphs . . . . .        | 42 |
| Spanned_Factors . . . . .          | 43 |
| summary.ATSMModelInputs . . . . .  | 44 |
| summary.ATSMModelOutputs . . . . . | 44 |
| TPDecompGraph . . . . .            | 45 |

|                             |    |
|-----------------------------|----|
| TradeFlows . . . . .        | 46 |
| TradeFlows_covid . . . . .  | 47 |
| Transition_Matrix . . . . . | 47 |
| VAR . . . . .               | 49 |
| Yields . . . . .            | 50 |
| Yields_covid . . . . .      | 50 |

Index
52

|          |                                  |
|----------|----------------------------------|
| autoplot | <i>Autoplot generic function</i> |
|----------|----------------------------------|

### Description

Autoplot generic function

### Usage

```
autoplot(x, ...)
```

### Arguments

|     |                                        |
|-----|----------------------------------------|
| x   | Object to plot                         |
| ... | Additional arguments passed to methods |

|                        |                                                  |
|------------------------|--------------------------------------------------|
| autoplot.ATSMModelBoot | <i>Autoplot method for ATSMModelBoot objects</i> |
|------------------------|--------------------------------------------------|

### Description

Autoplot method for ATSMModelBoot objects

### Usage

```
## S3 method for class 'ATSMModelBoot'
autoplot(x, NumOutPE, type, ...)
```

### Arguments

|          |                                                                                                                                                                                                                                                                       |
|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x        | An object of class 'ATSMModelBoot'                                                                                                                                                                                                                                    |
| NumOutPE | An object of class 'ATSMNumOutputs': point estimates of the numerical outputs                                                                                                                                                                                         |
| type     | Plot type: one of "IRF", "FEVD", "GIRF", "GFEVD" (each must be suffixed with "_Factors" or "_Yields"). For JLL-based models, an additional "_Ortho" suffix produces orthogonalized outputs. All inputs must end by "_Boot" as a reference to the bootstrap procedure. |
| ...      | Additional arguments (not used)                                                                                                                                                                                                                                       |

---

```
autoplot.ATSMNumOutputs
```

*Autoplot method for ATSMNumOutputs objects*

---

## Description

Autoplot method for ATSMNumOutputs objects

## Usage

```
## S3 method for class 'ATSMNumOutputs'
autoplot(x, type, ...)
```

## Arguments

|      |                                                                                                                                                                                                                                    |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x    | An object of class 'ATSMNumOutputs'                                                                                                                                                                                                |
| type | Plot type: "RiskFactors", "Fit", "TermPremia", or one of "IRF", "FEVD", "GIRF", "GFEVD" (each must be suffixed with "_Factors" or "_Yields"). For JLL-based models, an additional "_Ortho" suffix produces orthogonalized outputs. |
| ...  | Additional arguments (not used)                                                                                                                                                                                                    |

---

|                 |                                                                                                    |
|-----------------|----------------------------------------------------------------------------------------------------|
| Bias_Correc_VAR | <i>Estimates an unbiased VAR(1) using stochastic approximation (Bauer, Rudebusch and Wu, 2012)</i> |
|-----------------|----------------------------------------------------------------------------------------------------|

---

## Description

Estimates an unbiased VAR(1) using stochastic approximation (Bauer, Rudebusch and Wu, 2012)

## Usage

```
Bias_Correc_VAR(
  ModelType,
  BRWinputs,
  RiskFactors,
  Economies,
  FactorLabels,
  GVARinputs = NULL,
  JLLinputs = NULL,
  verbose = TRUE
)
```

**Arguments**

|              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ModelType    | character. Model type to be estimated. Permissible choices: "JPS original", "JPS global", "GVAR single", "JPS multi", "GVAR multi", "JLL original", "JLL No DomUnit", "JLL joint Sigma".                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| BRWinputs    | list. Contains the necessary inputs for the BRW model estimation: <ol style="list-style-type: none"> <li>1. Cent_Measure: "Mean" or "Median" (unbiased estimation type)</li> <li>2. gamma: Numeric. Adjustment parameter between 0 and 1. Default is 0.5.</li> <li>3. N_iter: Integer. Number of iterations for the stochastic approximation algorithm after burn-in. Default is 5000.</li> <li>4. N_burn: Integer. Number of burn-in iterations. Default is 15</li> <li>5. B: Integer. Number of bootstrap samples per iteration for calculating the noisy measure of the biased estimator's mean or median. Default is 50.</li> <li>6. check: Logical. Indicates whether to perform a closeness check. Default is TRUE.</li> <li>7. B_check: Integer. Number of bootstrap samples for the closeness check. Default is 100000.</li> <li>8. Eigen_rest: Numeric. Restriction on the largest eigenvalue under the P-measure. Default is 1.</li> </ol> |
| RiskFactors  | numeric matrix ( $T_d \times K$ ). Time series of risk factors.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Economies    | character vector. Names of the $C$ economies included in the system.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| FactorLabels | list. Labels for all variables in the model.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| GVARinputs   | list. Inputs for GVAR model estimation (see <a href="#">GVAR</a> ). Default is NULL.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| JLLinputs    | list. Inputs for JLL model estimation (see <a href="#">JLL</a> ). Default is NULL.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| verbose      | logical. Flag controlling function messaging. Default TRUE.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

**Value**

Bias-corrected VAR parameters based on the framework of Bauer, Rudebusch and Wu (2012). The list contains:

1. KOZ\_BC: estimated intercept ( $K \times 1$ );
2. K1Z\_BC: estimated feedback matrix ( $K \times K$ );
3. SSZ\_BC: estimated variance-covariance matrix ( $K \times K$ );
4. dist: root mean square distance (scalar);

**General Notation**

- $T_d$  denotes the model time series dimension.
- $C$  number of countries in the system.
- $K$  denotes the total number of risk factors.

## References

Bauer, Rudebusch and, Wu (2012). "Correcting Estimation Bias in Dynamic Term Structure Models"  
 This function offers an independent R implementation that is informed by the conceptual framework outlined in Bauer, Rudebusch and Wu (2012), but adapted to the present modeling context. Related Matlab routines are available on Cynthia Wu's website (<https://sites.google.com/view/jingcynthiawu/>).

## Examples

```
data(RiskFacFull)
Factors <- t(RiskFacFull[1:7, ])

BRWinputs <- list(
  Cent_Measure = "Mean", gamma = 0.4, N_iter = 1000, N_burn = 100,
  B = 10, check = 1, B_check = 5000
)

Economies <- "China"
N <- 3
ModelType <- "JPS original"
FactorLabels <- NULL

BRWpara <- Bias_Correc_VAR(ModelType, BRWinputs, Factors, Economies, FactorLabels, verbose = FALSE)
```

---

Bootstrap

*Generates the bootstrap-related outputs*

---

## Description

Generates the bootstrap-related outputs

## Usage

```
Bootstrap(
  ModelType,
  ModelParaPE,
  NumOutPE,
  Economies,
  InputsForOutputs,
  FactorLabels,
  JLLlist,
  GVARlist,
  WishBC = FALSE,
  BRWlist = NULL,
  Folder2save = NULL,
  verbose = TRUE
)
```

**Arguments**

|                  |                                                                                                                                                                                          |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ModelType        | character. Model type to be estimated. Permissible choices: "JPS original", "JPS global", "GVAR single", "JPS multi", "GVAR multi", "JLL original", "JLL No DomUnit", "JLL joint Sigma". |
| ModelParaPE      | list. Point estimates of the model parameters. See outputs from <a href="#">Optimization</a> .                                                                                           |
| NumOutPE         | list. Point estimates from numerical outputs. See outputs from <a href="#">NumOutputs</a> .                                                                                              |
| Economies        | character vector. Names of the C economies included in the system.                                                                                                                       |
| InputsForOutputs | list. Inputs for generating IRFs, GIRFs, FEVDs, GFEVDs, and Term Premia.                                                                                                                 |
| FactorLabels     | list. Labels for all variables present in the model, as returned by <a href="#">LabFac</a> .                                                                                             |
| JLLlist          | list. Inputs for JLL model estimation (see <a href="#">JLL</a> ). Default is NULL.                                                                                                       |
| GVARlist         | list. Inputs for GVAR model estimation (see <a href="#">GVAR</a> ). Default is NULL.                                                                                                     |
| WishBC           | logical. Whether to estimate the physical parameter model with bias correction (see <a href="#">Bias_Correc_VAR</a> ). Default is FALSE.                                                 |
| BRWlist          | list. Inputs for bias-corrected estimation (see <a href="#">Bias_Correc_VAR</a> ).                                                                                                       |
| Folder2save      | character. Folder path where outputs will be stored. Default saves outputs in a temporary directory.                                                                                     |
| verbose          | logical. Print progress messages. Default is TRUE.                                                                                                                                       |

**Value**

An object of class 'ATSMMModelBoot' containing:

- List of model parameters for each draw
- List of numerical outputs (IRFs, GIRFs, FEVDs, GFEVDs) for each draw
- Confidence bounds for the chosen level of significance

**Permissible options - Bootstrap list in InputsForOutputs**

- methodBS : "bs" (standard bootstrap), "wild" (wild bootstrap), "block" (block bootstrap)
- BlockLength : required input for the block bootstrap method. Block length must be larger than 0 and smaller than the model time series dimension (Td).
- ndraws: number of draws. Must be a positive integer.
- pctg : confidence level. Must be a positive integer. Common choices are: 68, 90 and 95.

**Available methods**

- autoplot(object, NumOutPE, type)

### Examples

```
data("ParaSetEx")
data("InpForOutEx")
data("NumOutEx")
ModelType <- "JPS original"
Economy <- "Brazil"
FacLab <- LabFac(N = 1, DomVar = "Eco_Act", GlobalVar = "Gl_Eco_Act", Economy, ModelType)

# Adjust Forecasting setting
InpForOutEx[[ModelType]]$Bootstrap <- list(
  WishBootstrap = 1, methodBS = "bs", BlockLength = 4,
  ndraws = 5, pctg = 95
)

Boot <- Bootstrap(ModelType, ParaSetEx, NumOutEx, Economy, InpForOutEx, FacLab,
  JLLlist = NULL,
  GVARlist = NULL, WishBC = FALSE, BRWlist = NULL, Folder2save = NULL, verbose = FALSE
)
```

---

|            |                                                                             |
|------------|-----------------------------------------------------------------------------|
| BR_jps_out | <i>Replications of the JPS (2014) outputs by Bauer and Rudebusch (2017)</i> |
|------------|-----------------------------------------------------------------------------|

---

### Description

Unspanned macro risk model outputs by Bauer and Rudebusch (2017)

### Usage

```
data("BR_jps_out")
```

### Format

Unspanned macro risk model outputs by Bauer and Rudebusch (2017)

**est.llk** summary list of log-likelihood estimations

**M.o** time series of unspanned factors

**pars** additional summary list of log-likelihood estimations

**W** Weight matrix that results from principal components analysis

**Y** time series of bond yields

**N** total number of risk factor of the model (spanned and unspanned)

**R** total number of spanned factor of the model

### References

Bauer, M. and Rudebusch, G. "Resolving the Spanning Puzzle in Macro-Finance Term Structure Models"

---

|              |                                                                                                                      |
|--------------|----------------------------------------------------------------------------------------------------------------------|
| DatabasePrep | <i>Gather data of several countries in a list. Particularly useful for GVAR-based setups (Compute "GVARFactors")</i> |
|--------------|----------------------------------------------------------------------------------------------------------------------|

---

## Description

Gather data of several countries in a list. Particularly useful for GVAR-based setups (Compute "GVARFactors")

## Usage

```
DatabasePrep(
  t_First,
  t_Last,
  Economies,
  N,
  FactorLabels,
  ModelType,
  Macro_FullData,
  Yields_FullData,
  Wgvar = NULL
)
```

## Arguments

|                 |                                                                                                                                                                                          |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| t_First         | character. Start date of the sample period in the format yyyy-mm-dd.                                                                                                                     |
| t_Last          | character. End date of the sample period in the format yyyy-mm-dd.                                                                                                                       |
| Economies       | character vector. Names of the C economies included in the system.                                                                                                                       |
| N               | positive integer. Number of country-specific spanned factors per country.                                                                                                                |
| FactorLabels    | list. Labels for all variables present in the model, as returned by <a href="#">LabFac</a> .                                                                                             |
| ModelType       | character. Model type to be estimated. Permissible choices: "JPS original", "JPS global", "GVAR single", "JPS multi", "GVAR multi", "JLL original", "JLL No DomUnit", "JLL joint Sigma". |
| Macro_FullData  | list. Full set of macroeconomic data, as returned by <a href="#">Load_Excel_Data</a> .                                                                                                   |
| Yields_FullData | list. Full set of bond yield data, as returned by <a href="#">Load_Excel_Data</a> .                                                                                                      |
| Wgvar           | GVAR transition matrix. For GVAR models, either a matrix (C x C) for fixed weights, or a named list of matrices for time-varying weights. Default is NULL. Required for GVAR models.     |

## Value

List containing the risk factor set for all countries and global factors. Particularly useful for GVAR-based models.

### General Notation

- C: number of countries in the system.
- N: number of country-specific spanned factors.

### Examples

```
# Load data from excel
macro_data <- Load_Excel_Data(system.file("extdata", "MacroData.xlsx", package = "MultiATSM"))
yields_data <- Load_Excel_Data(system.file("extdata", "YieldsData.xlsx", package = "MultiATSM"))
trade_data <- Load_Excel_Data(system.file("extdata", "TradeData.xlsx", package = "MultiATSM"))

# Adjust trade data
trade_data <- lapply(trade_data, function(df) {
  countries <- df[[1]]
  df <- as.data.frame(df[-1])
  rownames(df) <- countries
  df
})

# Define features of interest
ModelType <- "GVAR multi"
Economies <- c("China", "Uruguay", "Russia")
GlobalVar <- c("GBC", "CPI_OECD")
DomVar <- c("Eco_Act", "Inflation")
N <- 3
t0 <- "2006-09-01"
tF <- "2019-01-01"

# Compute some inputs
FactorLabels <- LabFac(N, DomVar, GlobalVar, Economies, ModelType)
Wgvar <- Transition_Matrix(
  t_First = "2006", t_Last = "2019", Economies,
  type = "Sample Mean", trade_data
)

# Compute GVARFactors
GVARFactors <- DatabasePrep(
  t0, tF, Economies, N, FactorLabels, ModelType, macro_data,
  yields_data, Wgvar
)
```

---

DataForEstimation

Retrieves data from Excel and builds the database used in the model estimation

---

### Description

Retrieves data from Excel and builds the database used in the model estimation

**Usage**

```
DataForEstimation(
  t0,
  tF,
  Economies,
  N,
  FactorLabels,
  ModelType,
  DataFrequency,
  Macro_FullData,
  Yields_FullData,
  DataConnect = NULL,
  W_type = NULL,
  t_First_Wgvar = NULL,
  t_Last_Wgvar = NULL
)
```

**Arguments**

|                              |                                                                                                                                                                                          |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>t0</code>              | character. Start date of the sample period in the format yyyy-mm-dd.                                                                                                                     |
| <code>tF</code>              | character. End date of the sample period in the format yyyy-mm-dd.                                                                                                                       |
| <code>Economies</code>       | character vector. Names of the C economies included in the system.                                                                                                                       |
| <code>N</code>               | positive integer. Number of country-specific spanned factors.                                                                                                                            |
| <code>FactorLabels</code>    | list. Labels for all variables present in the model, as returned by <a href="#">LabFac</a> .                                                                                             |
| <code>ModelType</code>       | character. Model type to be estimated. Permissible choices: "JPS original", "JPS global", "GVAR single", "JPS multi", "GVAR multi", "JLL original", "JLL No DomUnit", "JLL joint Sigma". |
| <code>DataFrequency</code>   | character. Data frequency. Permissible choices: "Daily All Days", "Daily Business Days", "Weekly", "Monthly", "Quarterly", "Annually".                                                   |
| <code>Macro_FullData</code>  | list. Full set of macroeconomic data.                                                                                                                                                    |
| <code>Yields_FullData</code> | list. Full set of bond yield data.                                                                                                                                                       |
| <code>DataConnect</code>     | list. Data for computing bilateral connectedness measures. Default is NULL. Required for GVAR-based models.                                                                              |
| <code>W_type</code>          | character. Weight matrix type. Permissible choices: "Full Sample" (all years), "Sample Mean" (average over sample), or a specific year (e.g. "1998", "2005"). Default is NULL.           |
| <code>t_First_Wgvar</code>   | character. First year for weight matrix computation. Default is NULL.                                                                                                                    |
| <code>t_Last_Wgvar</code>    | character. Last year for weight matrix computation. Default is NULL.                                                                                                                     |

**Value**

A list containing:

1. Yields: matrix ( $J \times T_d$  or  $CJ \times T_d$ ) of bond yields for all countries.

2. RiskFactors: matrix ( $K \times T_d$ ) of risk factors for all countries.
3. GVARFactors: list of variables used in VARX estimation (see GVARFactors data file). NULL if not GVAR-based.

### General Notation

- $T_d$ : model time series dimension.
- $C$ : number of countries in the system.
- $N$ : number of country-specific spanned factors.
- $K$ : total number of risk factors.
- $J$ : number of bond yields per country used in estimation.

### See Also

[Load\\_Excel\\_Data](#)

### Examples

```
DomVar <- c("Eco_Act", "Inflation")
GlobalVar <- c("GBC", "CPI_OECD")
t0 <- "2006-09-01"
tF <- "2019-01-01"
Economies <- c("China", "Brazil", "Mexico", "Uruguay", "Russia")
N <- 2
ModelType <- "JPS original"
FactorLabels <- LabFac(N, DomVar, GlobalVar, Economies, ModelType)
DataFrequency <- "Monthly"
MacroData <- Load_Excel_Data(system.file("extdata", "MacroData.xlsx", package = "MultiATSM"))
YieldData <- Load_Excel_Data(system.file("extdata", "YieldsData.xlsx", package = "MultiATSM"))
DataModel <- DataForEstimation(
  t0, tF, Economies, N, FactorLabels, ModelType, DataFrequency,
  MacroData, YieldData
)
```

---

DomMacro

*Data: domestic risk factors - Candelon and Moura (2024, JFEC)*


---

### Description

Domestic risk factors data used in Candelon and Moura (2024, JFEC)

### Usage

```
data("DomMacro")
```

**Format**

A matrix of country-specific risk factors (inflation and economic activity growth) for Brazil, China, Mexico, and Uruguay. The data have monthly frequency and span the period from June/2004 to January/2020.

**Source**

**Inflation** year-over-year variation from Consumer price index published by the International Monetary Fund <<https://data.imf.org/en/datasets/IMF.STA:CPI>>

**Economic activity** GDP leading indicator published by the OECD <<https://www.oecd.org/en/data/indicators/composite-leading-indicator-cli.html>>

**References**

Candelon, B. and Moura, R. (2024) "A Multicountry Model of the Term Structures of Interest Rates with a GVAR". (Journal of Financial Econometrics)

---

DomMacro\_covid

*Data: Risk Factors for the GVAR - Candelon and Moura (2023)*


---

**Description**

Domestic risk factors data used in the GVAR models - Candelon and Moura (2023)

**Usage**

```
data("DomMacro_covid")
```

**Format**

A matrix of country-specific risk factors (inflation, output growth, CDS, and COVID-19 reproduction rate) for Brazil, India, Mexico, and Russia. The data have weekly frequency and span the period from March 22, 2020, to September 26, 2021.

**Source**

**Inflation** Monthly CPI (from OECD) interpolated to daily data (spline), converted to weekly year-over-year changes, and detrended <<https://www.oecd.org/en/data/indicators/inflation-cpi.html>>

**Output growth** Detrended weekly estimate of GDP year-over-year growth derived from the OECD Weekly Tracker index <<https://web-archive.oecd.org/sections/weekly-tracker-of-gdp-growth/index.htm>>

**CDS** 5-year maturity CDS. Simulated data constructed using Bloomberg bond yield series.

**COVID-19 reproduction rate** detrended R rate from the Our World in Data database <<https://ourworldindata.org/coronavirus>>

**References**

Candelon, B. and Moura, R. (2023) "Sovereign yield curves and the COVID-19 in emerging markets". (Economic Modelling)

---

FEVDandGFEVDgraphs      *FEVD and GFEVD graphs for all models*


---

## Description

FEVD and GFEVD graphs for all models

## Usage

```
FEVDandGFEVDgraphs(  
  ModelType,  
  NumOut,  
  WishPdynamicsgraphs,  
  WishYieldsgraphs,  
  FEVDhoriz,  
  PathsGraphs,  
  OutputType,  
  Economies,  
  Folder2save,  
  verbose  
)
```

## Arguments

|                     |                                                                                                                                                                                    |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ModelType           | character. Estimated model type. Permissible choices: "JPS original", "JPS global", "GVAR single", "JPS multi", "GVAR multi", "JLL original", "JLL No DomUnit", "JLL joint Sigma". |
| NumOut              | list. Computed outputs containing model fit, IRFs, FEVDs, GIRFs, GFEVDs and Term premia.                                                                                           |
| WishPdynamicsgraphs | logical. Set TRUE to generate risk factor graphs, FALSE otherwise.                                                                                                                 |
| WishYieldsgraphs    | logical. Set TRUE to generate bond yield graphs, FALSE otherwise.                                                                                                                  |
| FEVDhoriz           | integer. Desired horizon of analysis for the FEVDs.                                                                                                                                |
| PathsGraphs         | character. Path of the folder in which the graphs will be saved.                                                                                                                   |
| OutputType          | character. Available options: "FEVD", "GFEVD", "FEVD Ortho", "GFEVD Ortho".                                                                                                        |
| Economies           | character vector. Names of the C economies included in the system.                                                                                                                 |
| Folder2save         | character. Folder path where the outputs will be stored.                                                                                                                           |
| verbose             | logical. Flag controlling function messaging.                                                                                                                                      |

**Available Methods**

- 'autoplot(object, type = "FEVD\_Factor")', 'autoplot(object, type = "FEVD\_Yields")', 'autoplot(object, type = "GFEVD\_Yields")', 'autoplot(object, type = "GFEVD\_Yields")'. For JLL-based models: 'autoplot(object, type = "FEVD\_Factor\_Ortho")', 'autoplot(object, type = "FEVD\_Yields\_Ortho")', 'autoplot(object, type = "GFEVD\_Yields\_Ortho")', 'autoplot(object, type = "GFEVD\_Yields\_Ortho")'.

**Examples**

```
data("NumOutEx")
ModelType <- "JPS original"
Economy <- "Brazil"
FEVDhoriz <- 20
FEVDandGFEVDgraphs(ModelType, NumOutEx,
  WishPdynamicsgraphs = FALSE, WishYieldsgraphs = TRUE, FEVDhoriz,
  PathsGraphs = NULL, OutputType = "FEVD", Economy,
  Folder2save = NULL, verbose = FALSE
)
```

Fitgraphs

*Model fit graphs for all models***Description**

Model fit graphs for all models

**Usage**

```
Fitgraphs(
  ModelType,
  WishFitgraphs,
  ModelPara,
  NumOut,
  Economies,
  PathsGraphs,
  Folder2save,
  verbose
)
```

**Arguments**

|               |                                                                                 |
|---------------|---------------------------------------------------------------------------------|
| ModelType     | character. Estimated model type.                                                |
| WishFitgraphs | logical. Set TRUE to generate fit graphs, FALSE otherwise.                      |
| ModelPara     | list. Model parameter estimates (see <a href="#">Optimization</a> ).            |
| NumOut        | list. Outputs containing model fit, IRFs, FEVDs, GIRFs, GFEVDs and Term premia. |

|             |                                                                  |
|-------------|------------------------------------------------------------------|
| Economies   | character vector. Names of the economies included in the system. |
| PathsGraphs | character. Path of the folder in which the graphs will be saved. |
| Folder2save | character. Desired folder path to save outputs.                  |
| verbose     | logical. Flag controlling function messaging.                    |

### Available Methods

- 'autoplot(object, type = "Fit")'

### Examples

```
data("ParaSetEx")
data("NumOutEx")
ModelType <- "JPS original"
Economy <- "Brazil"
Fitgraphs(ModelType,
  WishFitgraphs = TRUE, ParaSetEx, NumOutEx, Economy, PathsGraphs = NULL,
  Folder2save = NULL, verbose = FALSE
)
```

---

ForecastYields

*Generates forecasts of bond yields for all model types*


---

### Description

Generates forecasts of bond yields for all model types

### Usage

```
ForecastYields(
  ModelType,
  ModelPara,
  InputsForOutputs,
  FactorLabels,
  Economies,
  JLLlist = NULL,
  GVARlist = NULL,
  WishBRW = FALSE,
  BRWlist = NULL,
  Folder2save = NULL,
  verbose = TRUE
)
```

**Arguments**

|                  |                                                                                                                                                                                          |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ModelType        | character. Model type to be estimated. Permissible choices: "JPS original", "JPS global", "GVAR single", "JPS multi", "GVAR multi", "JLL original", "JLL No DomUnit", "JLL joint Sigma". |
| ModelPara        | list. Point estimates of the model parameters. See outputs from <a href="#">Optimization</a> .                                                                                           |
| InputsForOutputs | list. Inputs for generating IRFs, GIRFs, FEVDs, GFEVDs, and Term Premia.                                                                                                                 |
| FactorLabels     | list. Labels for all variables present in the model, as returned by <a href="#">LabFac</a> .                                                                                             |
| Economies        | character vector. Names of the C economies included in the system.                                                                                                                       |
| JLLlist          | list. Inputs for JLL model estimation (see <a href="#">JLL</a> ). Default is NULL.                                                                                                       |
| GVARlist         | list. Inputs for GVAR model estimation (see <a href="#">GVAR</a> ). Default is NULL.                                                                                                     |
| WishBRW          | logical. Whether to estimate the physical parameter model with bias correction (see <a href="#">Bias_Correc_VAR</a> ). Default is FALSE.                                                 |
| BRWlist          | list. Inputs for bias-corrected estimation (see <a href="#">Bias_Correc_VAR</a> ).                                                                                                       |
| Folder2save      | character. Folder path where outputs will be stored. Default saves outputs in a temporary directory.                                                                                     |
| verbose          | logical. Print progress messages. Default is TRUE.                                                                                                                                       |

**Value**

An object of class 'ATSMModelForecast' containing the following elements:

1. Out-of-sample forecasts of bond yields per forecast horizon
2. Out-of-sample forecast errors of bond yields per forecast horizon
3. Root mean square errors per forecast horizon

**Permissible options - forecast list (InputsForOutputs input)**

- ForHoriz: forecast horizon. Must be a positive integer.
- t0Sample: initial sample date. Must be a positive integer smaller than the time series dimension of the model (Td)
- t0Forecast: last sample date for the first forecast. Note that  $Td > t0Forecast + ForHoriz$ .
- ForType: "Rolling" (rolling window forecast) or "Expanding" (for expanding window forecast)

**Available Methods**

- 'plot(object)'

### Examples

```
data("ParaSetEx")
data("InpForOutEx")
# Adjust inputs according to the loaded features
ModelType <- "JPS original"
Economy <- "Brazil"
FacLab <- LabFac(N = 1, DomVar = "Eco_Act", GlobalVar = "Gl_Eco_Act", Economy, ModelType)
# Adjust Forecasting setting
InpForOutEx[[ModelType]]$Forecasting <- list(
  WishForecast = 1, ForHoriz = 12, t0Sample = 1,
  t0Forecast = 143, ForType = "Expanding"
)

Forecast <- ForecastYields(ModelType, ParaSetEx, InpForOutEx, FacLab, Economy,
  WishBRW = FALSE, verbose = TRUE
)
```

---

GlobalMacro

*Data: Risk Factors - Candelon and Moura (2024, JFEC)*


---

### Description

Global risk factors data used in Candelon and Moura (2024, JFEC)

### Usage

```
data("GlobalMacro")
```

### Format

A matrix containing the time series of global risk factors, namely global economic activity and global inflation. The data have monthly frequency and span the period from June/2004 to January/2020.

### Source

**Global economic activity** Lutz Kilian's index of global real economic activity <<https://sites.google.com/site/lkilian2019/resets?authuser=0>>

**Global inflation** year-over-year variation of the OECD aggregated CPI containing all its state members <<https://www.oecd.org/en/data/indicators/inflation-cpi.html>>

### References

Candelon, B. and Moura, R. (2024) "A Multicountry Model of the Term Structures of Interest Rates with a GVAR". (Journal of Financial Econometrics)

---

|                   |                                                           |
|-------------------|-----------------------------------------------------------|
| GlobalMacro_covid | <i>Data: Risk Factors - Candelon and Moura (2023, EM)</i> |
|-------------------|-----------------------------------------------------------|

---

**Description**

Global risk factors data used in Candelon and Moura (2023)

**Usage**

```
data("GlobalMacro_covid")
```

**Format**

A matrix containing the time series of global risk factors, namely the year-over-year growth rates of U.S. and Chinese output, and the S&P 500 index. The data have weekly frequency and span the period from March 22, 2020, to September 26, 2021.

**Source**

**U.S. output growth:** OECD Weekly Tracker index <<https://web-archive.oecd.org/sections/weekly-tracker-of-gdp-growth/index.htm>>

**China output growth:** weekly year-over-year change in the interpolated OECD leading indicator <<https://www.oecd.org/en/data/indicators/composite-leading-indicator-cli.html>>

**S&P-500:** year-over-year variation from the Standard and Poor's 500 stock market index. Simulated data constructed using FRED series.

**References**

Candelon, B. and Moura, R. (2023) "Sovereign yield curves and the COVID-19 in emerging markets". (Economic Modelling)

---

|      |                                                   |
|------|---------------------------------------------------|
| GVAR | <i>Estimates a GVAR(1) and VARX(1,1,1) models</i> |
|------|---------------------------------------------------|

---

**Description**

Estimates a GVAR(1) and VARX(1,1,1) models

**Usage**

```
GVAR(GVARinputs, N, CheckInputs = FALSE)
```

## Arguments

|             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| GVARinputs  | list. Inputs for GVAR model estimation: <ol style="list-style-type: none"> <li>1. Economies: character vector. Contains the C names of the economies included in the system.</li> <li>2. GVARFactors: list. All variables used in the estimation of the VARX model (see e.g. GVARFactors file for details);</li> <li>3. VARXtype: Permissible: <ul style="list-style-type: none"> <li>• 'unconstrained': model is estimated without constraints (each equation is estimated individually by ordinary least square);</li> <li>• 'constrained: Spanned Factors': The model is estimated with the restriction that foreign pricing factors do NOT affect (i) domestic economic variables and (ii) domestic pricing factors (estimation via restricted least squares).</li> <li>• 'constrained : [factor_name]': The model is estimated with the restriction that the specified risk factor is influenced only by its own lagged values and the lagged values of its corresponding star variables. (estimation via restricted least squares.)</li> </ul> </li> <li>4. Wgvar: The GVAR transition matrix (<math>C \times C</math>) used in the model solution. (See the output from the <a href="#">Transition_Matrix</a> function.).</li> </ol> |
| N           | positive integer. Number of country-specific spanned factors.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| CheckInputs | logical. Whether to perform a prior consistency check on the inputs provided in GVARinputs. Default is FALSE.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

## Value

list. Contains:

1. parameters of the country-specific VARX(1,1,1):
  - intercept ( $M + N \times 1$ )
  - phi\_1 ( $M + N \times M + N$ )
  - phi\_1\* ( $M + N \times M + N$ )
  - phi\_g ( $M + N \times M + N$ )
  - Sigma ( $M + N \times G$ )
2. parameters of the GVAR:
  - F0 ( $K \times K$ )
  - F1 ( $K \times K$ )
  - Sigma\_y ( $K \times K$ )

## General Notation

- C: number of countries in the system
- G: number of global unspanned factors
- M: number of country-specific unspanned factors
- N: number of country-specific spanned factors
- K: total number of risk factors ( $K = C \times (N + M) + G$ )

## References

Chudik, A. and Pesaran, M. H. (2016). "Theory and Practice of GVAR modelling" (Journal of Economic Surveys)

## Examples

```
data(GVARFactors)

GVARinputs <- list(
  Economies = c("China", "Brazil", "Mexico", "Uruguay"),
  GVARFactors = GVARFactors, VARXtype = "unconstrained"
)

GVARinputs$Wgvar <- matrix(c(
  0, 0.83, 0.86, 0.38,
  0.65, 0, 0.13, 0.55,
  0.32, 0.12, 0, 0.07,
  0.03, 0.05, 0.01, 0
), nrow = 4, ncol = 4)
N <- 3

GVARPara <- GVAR(GVARinputs, N)
```

---

GVARFactors

*Data: Risk Factors for the GVAR - Candelon and Moura (2024, JFEC)*


---

## Description

Risk factors data used in the GVAR-ATSM from Candelon and Moura (2024, JFEC)

## Usage

```
data("GVARFactors")
```

## Format

List of risk factors organized for GVAR estimation. It includes global unspanned factors (economic activity, inflation) and domestic factors—both unspanned (economic activity, inflation) and spanned (level, slope, curvature) with their starred counterparts. The dataset covers Brazil, China, Mexico, and Uruguay at a monthly frequency from June 2004 to January 2020.

## Source

**Global unspanned factors** See `data("GlobalMacro")` for a detailed data description.

**Domestic unspanned factors** See `data("DomMacro")` for a detailed data description.

**Domestic spanned factors** First three principal components of each country set of bond yields. See `data("Yields")` for a detailed data description.

**Domestic star factors** Weighted average of foreign factors. See [Transition\\_Matrix](#) for the computation of weights.

References

Cadelon, B. and Moura, R. (2024) "A Multicountry Model of the Term Structures of Interest Rates with a GVAR". (Journal of Financial Econometrics)

---

|             |                                                                                 |
|-------------|---------------------------------------------------------------------------------|
| InpForOutEx | <i>Example of list inputs used in the construction of several model outputs</i> |
|-------------|---------------------------------------------------------------------------------|

---

Description

List of inputs of a JPS-based model for Brazilian data

Usage

```
data("InpForOutEx")
```

Format

list of inputs

---

|              |                                                                                       |
|--------------|---------------------------------------------------------------------------------------|
| InputsForOpt | <i>Generates inputs necessary to build the likelihood function for the ATSM model</i> |
|--------------|---------------------------------------------------------------------------------------|

---

Description

Generates inputs necessary to build the likelihood function for the ATSM model

Usage

```
InputsForOpt(  
  InitialSampleDate,  
  FinalSampleDate,  
  ModelType,  
  Yields,  
  GlobalMacro,  
  DomMacro,  
  FactorLabels,  
  Economies,  
  DataFrequency,  
  GVARlist = NULL,  
  JLLlist = NULL,  
  WishBRW = FALSE,
```

```

BRWlist = NULL,
UnitYields = "Month",
CheckInputs = TRUE,
BS_Adj = FALSE,
verbose = TRUE
)

```

## Arguments

|                   |                                                                                                                                                                                          |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| InitialSampleDate | Start date of the sample period in the format "dd-mm-yyyy"                                                                                                                               |
| FinalSampleDate   | End date of the sample period in the format "dd-mm-yyyy"                                                                                                                                 |
| ModelType         | character. Model type to be estimated. Permissible choices: "JPS original", "JPS global", "GVAR single", "JPS multi", "GVAR multi", "JLL original", "JLL No DomUnit", "JLL joint Sigma". |
| Yields            | numerical matrix with time series of yields ( $J \times Td$ or $CJ \times Td$ )                                                                                                          |
| GlobalMacro       | numerical matrix with time series of the global risk factors ( $G \times Td$ )                                                                                                           |
| DomMacro          | numerical matrix with time series of the country-specific risk factors for all C countries ( $C \times Td$ or $CM \times Td$ )                                                           |
| FactorLabels      | list. Labels for all variables present in the model, as returned by <a href="#">LabFac</a> .                                                                                             |
| Economies         | character vector. Names of the C economies included in the system.                                                                                                                       |
| DataFrequency     | character. Data frequency. Permissible choices: "Daily All Days", "Daily Business Days", "Weekly", "Monthly", "Quarterly", "Annually".                                                   |
| GVARlist          | list. Inputs for GVAR model estimation. See details below.                                                                                                                               |
| JLLlist           | list. Inputs for JLL model estimation. See details below.                                                                                                                                |
| WishBRW           | logical. Whether to estimate the physical parameter model with bias correction (see <a href="#">Bias_Correc_VAR</a> ). Default is FALSE.                                                 |
| BRWlist           | list. Inputs for bias-corrected estimation.                                                                                                                                              |
| UnitYields        | character. Maturity unit of yields. Permissible choices: "Month" or "Year". Default is "Month".                                                                                          |
| CheckInputs       | logical. Whether to perform a prior check on the consistency of the provided input list. Default is TRUE.                                                                                |
| BS_Adj            | logical. Whether to adjust the global series for the sepQ models in the Bootstrap setting. Default is FALSE.                                                                             |
| verbose           | logical. Print progress messages. Default is TRUE.                                                                                                                                       |

## Value

An object of class 'ATSMModelInputs' containing the necessary inputs for performing the model optimization.

**Permissible options for GVARlist**

- VARXtype: "unconstrained" or "constrained"
- W\_type: "Time-varying" or "Sample Mean"
- t\_First\_Wgvar, t\_Last\_Wgvar: year as character

**Permissible options for JLLlist**

- DomUnit: name of the dominant economy or None
- WishSigmas: TRUE (estimate variance-covariance matrices) or FALSE
- SigmaNonOrtho: NULL or K x K matrix

**Permissible options for BRWlist**

- BiasCorrection: TRUE (bias-corrected) or FALSE
- flag\_mean: TRUE (mean) or FALSE (median)
- gamma: numeric adjustment parameter
- N\_iter: number of iterations
- N\_burn: number of burn-in iterations
- B: number of bootstrap samples
- checkBRW: TRUE or FALSE
- B\_check: number of bootstrap samples for closeness check

**General Notation**

- Td model time series dimension.
- C number of countries in the system.
- G number of global unspanned factors.
- M number of country-specific unspanned factors.
- K total number of risk factors.
- J number of bond yields per country used in estimation.

**Available Methods**

- 'print(object)' - 'summary(object)'

**Examples**

```
# Example 1:
data(GlobalMacro)
data(DomMacro)
data(Yields)

ModelType <- "JPS original"
Economies <- "Mexico"
t0 <- "01-05-2007" # Initial Sample Date (Format: "dd-mm-yyyy")
```

```

tF <- "01-12-2018" # Final Sample Date (Format: "dd-mm-yyyy")
N <- 3
GlobalVar <- c("G1_Eco_Act") # Global Variables
DomVar <- c("Eco_Act") # Domestic Variables
FactorLabels <- LabFac(N, DomVar, GlobalVar, Economies, ModelType)

DataFreq <- "Monthly"

ATSMInputs <- InputsForOpt(t0, tF, ModelType, Yields, GlobalMacro, DomMacro,
  FactorLabels, Economies, DataFreq,
  CheckInputs = FALSE, verbose = FALSE
)

# Example 2:
LoadData("CM_2024")

ModelType <- "GVAR multi"

Economies <- c("China", "Brazil", "Mexico", "Uruguay")
t0 <- "01-05-2007" # InitialSampleDate (Format: "dd-mm-yyyy")
tF <- "01-12-2019" # FinalSampleDate (Format: "dd-mm-yyyy")
N <- 2
GlobalVar <- c("G1_Eco_Act", "G1_Inflation") # Global Variables
DomVar <- c("Inflation") # Domestic Variables
FactorLabels <- LabFac(N, DomVar, GlobalVar, Economies, ModelType)

DataFreq <- "Monthly"
GVARlist <- list(
  VARXtype = "unconstrained", W_type = "Sample Mean",
  t_First_Wgvar = "2007", t_Last_Wgvar = "2019", DataConnectedness = TradeFlows
)

ATSMInputs <- InputsForOpt(t0, tF, ModelType, Yields, GlobalMacro, DomMacro,
  FactorLabels, Economies, DataFreq, GVARlist,
  CheckInputs = FALSE, verbose = FALSE
)

# Example 3:
LoadData("CM_2024")

ModelType <- "JLL original"

Economies <- c("China", "Brazil", "Uruguay")
t0 <- "01-05-2007" # InitialSampleDate (Format: "dd-mm-yyyy")
tF <- "01-12-2019" # FinalSampleDate (Format: "dd-mm-yyyy")
N <- 2
GlobalVar <- c("G1_Eco_Act", "G1_Inflation") # Global Variables
DomVar <- c("Eco_Act", "Inflation") # Domestic Variables
FactorLabels <- LabFac(N, DomVar, GlobalVar, Economies, ModelType)

JLLinputs <- list(DomUnit = "China")

DataFrequency <- "Monthly"

```

```

ATSMInputs <- InputsForOpt(t0, tF, ModelType, Yields, GlobalMacro, DomMacro,
  FactorLabels, Economies, DataFreq,
  JLLlist = JLLinputs,
  CheckInputs = FALSE, verbose = FALSE
)

```

---

|                  |                                                                                           |
|------------------|-------------------------------------------------------------------------------------------|
| InputsForOutputs | <i>Collects the inputs that are used to construct the numerical and graphical outputs</i> |
|------------------|-------------------------------------------------------------------------------------------|

---

### Description

Collects the inputs that are used to construct the numerical and graphical outputs

### Usage

```

InputsForOutputs(
  ModelType,
  Horiz,
  ListOutputWished,
  OutputLabel,
  WishStationarityQ,
  DataFrequency,
  WishGraphYields = FALSE,
  WishGraphRiskFactors = FALSE,
  WishOrthoJLLgraphs = FALSE,
  WishForwardPremia = FALSE,
  LimFP = NULL,
  WishBootstrap = FALSE,
  ListBoot = NULL,
  WishForecast = FALSE,
  ListForecast = NULL,
  UnitYields = "Month"
)

```

### Arguments

|                  |                                                                                                                                                                                          |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ModelType        | character. Model type to be estimated. Permissible choices: "JPS original", "JPS global", "GVAR single", "JPS multi", "GVAR multi", "JLL original", "JLL No DomUnit", "JLL joint Sigma". |
| Horiz            | numeric scalar. Desired analysis horizon for the outputs.                                                                                                                                |
| ListOutputWished | character vector. Desired graphical outputs. Available options: "RiskFactors", "Fit", "IRF", "FEVD", "GIRF", "GFEVD", "TermPremia", "ForwardPremia".                                     |
| OutputLabel      | character. Name of the output label to be stored.                                                                                                                                        |

|                      |                                                                                                                                        |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| WishStationarityQ    | logical. Whether to impose that the largest eigenvalue under Q is strictly smaller than 1. TRUE to impose.                             |
| DataFrequency        | character. Data frequency. Permissible choices: "Daily All Days", "Daily Business Days", "Weekly", "Monthly", "Quarterly", "Annually". |
| WishGraphYields      | logical. Whether to generate graphs for yields. Default is FALSE.                                                                      |
| WishGraphRiskFactors | logical. Whether to generate graphs for risk factors. Default is FALSE.                                                                |
| WishOrthoJLLgraphs   | logical. Whether to generate orthogonalized JLL-based graphs. Default is FALSE.                                                        |
| WishForwardPremia    | logical. Whether to generate forward premia graphs. Default is FALSE.                                                                  |
| LimFP                | numeric vector. Maturities associated with the start and end dates of the loan.                                                        |
| WishBootstrap        | logical. Whether to perform bootstrap-based estimation. Default is FALSE.                                                              |
| ListBoot             | list. Contains bootstrap settings: methodBS ("bs", "wild", "block"), BlockLength (numeric), ndraws (numeric), pctg (numeric).          |
| WishForecast         | logical. Whether to generate forecasts. Default is FALSE.                                                                              |
| ListForecast         | list. Contains forecast settings: ForHoriz (numeric), t0Sample (numeric), t0Forecast (numeric), ForType ("Rolling", "Expanding").      |
| UnitYields           | character. Maturity unit of yields. Options: "Month" or "Year". Default is "Month".                                                    |

## Value

List of necessary inputs to generate the graphs and outputs of the desired model.

## Examples

```

ModelType <- "JPS original"
Horiz <- 100
DesiredOutputGraphs <- c("Fit", "GIRF", "GFEVD")
OutputLabel <- "Test"
WishStationarityQ <- TRUE
WishGraphRiskFac <- FALSE
WishGraphYields <- TRUE

InputsList <- InputsForOutputs(
  ModelType, Horiz, DesiredOutputGraphs, OutputLabel,
  WishStationarityQ, WishGraphYields, WishGraphRiskFac
)
```

IRFandGIRFgraphs

*IRF and GIRF graphs for all models***Description**

IRF and GIRF graphs for all models

**Usage**

```
IRFandGIRFgraphs(
  ModelType,
  NumOut,
  WishPdynamicsgraphs,
  WishYieldsgraphs,
  IRFhoriz,
  PathsGraphs,
  OutputType,
  Economies,
  Folder2save,
  verbose
)
```

**Arguments**

|                     |                                                                                                                                                                                    |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ModelType           | character. Estimated model type. Permissible choices: "JPS original", "JPS global", "GVAR single", "JPS multi", "GVAR multi", "JLL original", "JLL No DomUnit", "JLL joint Sigma". |
| NumOut              | list. Computed outputs containing model fit, IRFs, FEVDs, GIRFs, GFEVDs and term premia.                                                                                           |
| WishPdynamicsgraphs | logical. Set TRUE to generate risk factor graphs, FALSE otherwise.                                                                                                                 |
| WishYieldsgraphs    | logical. Set TRUE to generate bond yield graphs, FALSE otherwise.                                                                                                                  |
| IRFhoriz            | integer. Desired horizon of analysis for the IRFs.                                                                                                                                 |
| PathsGraphs         | character. Path of the folder in which the graphs will be saved.                                                                                                                   |
| OutputType          | character. Available options: "IRF", "GIRF", "IRF Ortho", "GIRF Ortho".                                                                                                            |
| Economies           | character vector. Names of the C economies included in the system.                                                                                                                 |
| Folder2save         | character. Folder path where the outputs will be stored.                                                                                                                           |
| verbose             | logical. Flag controlling function messaging.                                                                                                                                      |

**Available Methods**

- 'autoplot(object, type = "IRF\_Factor")', 'autoplot(object, type = "IRF\_Yields")', 'autoplot(object, type = "GIRF\_Yields")', 'autoplot(object, type = "GIRF\_Yields")'. For JLL-based models: 'autoplot(object, type = "IRF\_Factor\_Ortho")', 'autoplot(object, type = "IRF\_Yields\_Ortho")', 'autoplot(object, type = "GIRF\_Yields\_Ortho")', 'autoplot(object, type = "GIRF\_Yields\_Ortho")'.

**Examples**

```

data("NumOutEx")
ModelType <- "JPS original"
Economy <- "Brazil"
IRFhoriz <- 20
irf_Out <- IRFandGIRFgraphs(ModelType, NumOutEx,
  WishPdynamicsgraphs = FALSE, WishYieldsgraphs = TRUE, IRFhoriz,
  PathsGraphs = NULL, OutputType = "GIRF", Economy, Folder2save = NULL,
  verbose = FALSE
)

```

JLL

*Estimates the P-dynamics from JLL-based models***Description**

Estimates the P-dynamics from JLL-based models

**Usage**

```
JLL(NonOrthoFactors, N, JLLinputs, CheckInputs = FALSE)
```

**Arguments**

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NonOrthoFactors | numeric matrix (K x Td). Time series of risk factors before orthogonalization.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| N               | positive integer. Number of country-specific spanned factors.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| JLLinputs       | list. Necessary inputs to estimate JLL models: <ol style="list-style-type: none"> <li>1. Economies: character vector. Set of C economies in the system.</li> <li>2. DomUnit: character. Name of the dominant economy, or "None" if not assigned (for "JLL No DomUnit" model).</li> <li>3. WishSigmas: logical. TRUE to estimate variance-covariance matrices and Cholesky factorizations; FALSE otherwise.</li> <li>4. SigmaNonOrtho: NULL or F x F matrix from non-orthogonalized dynamics.</li> <li>5. JLLModelType: character. Permissible choices: "JLL original", "JLL joint Sigma", "JLL No DomUnit".</li> </ol> |
| CheckInputs     | logical. Whether to perform a prior consistency check on the inputs provided in JLLinputs. Default is FALSE.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

**Value**

List of model parameters from both the orthogonalized and non-orthogonalized versions of the JLL-based models

General Notation

- Td: model time series dimension
- C number of countries in the system.
- K: total number of risk factors

References

Jotiskhatira, P. ; Le, A. and Lundblad, C. (2015). "Why do interest rates in different currencies co-move?" (Journal of Financial Economics)

Examples

```
data(RiskFacFull)
RF_TS <- RiskFacFull
N <- 3
JLLinputs <- list(
  Economies = c("China", "Brazil", "Mexico", "Uruguay"), DomUnit = "China",
  WishSigmas = TRUE, SigmaNonOrtho = NULL, JLLModelType = "JLL original"
)
JLLPara <- JLL(RF_TS, N, JLLinputs)
```

---

|        |                                                                |
|--------|----------------------------------------------------------------|
| LabFac | <i>Generates the labels for risk factors used in the model</i> |
|--------|----------------------------------------------------------------|

---

Description

Generates the labels for risk factors used in the model

Usage

```
LabFac(N, DomVar, GlobalVar, Economies, ModelType)
```

Arguments

|           |                                                                                                                                                                                          |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| N         | positive integer. Number of country-specific spanned factors. Must be between 1 and 8.                                                                                                   |
| DomVar    | character vector. Names of the domestic variables.                                                                                                                                       |
| GlobalVar | character vector. Names of the global variables.                                                                                                                                         |
| Economies | character vector. Names of the economies included in the system.                                                                                                                         |
| ModelType | character. Model type to be estimated. Permissible choices: "JPS original", "JPS global", "GVAR single", "JPS multi", "GVAR multi", "JLL original", "JLL No DomUnit", "JLL joint Sigma". |

**Value**

List containing the risk factor labels for spanned, domestic, star, and global variables, as well as tables for each country and all countries.

**Examples**

```
N <- 2
DomVar <- c("inflation", "Output gap")
GlobalVar <- "Commodity Prices"
Economies <- c("U.S.", "Canada", "Germany", "Japan")
ModelType <- "JPS original"
VarLabels <- LabFac(N, DomVar, GlobalVar, Economies, ModelType)
```

---

LoadData

*Loads data sets from several papers*


---

**Description**

Loads data sets from several papers

**Usage**

```
LoadData(DataPaper)
```

**Arguments**

DataPaper      Available options are BR\_2017 (Bauer and Rudebusch, 2017) , CM\_2023 (Candelon and Moura, 2023), CM\_2024 (Candelon and Moura, 2024)

**Value**

Complete set of data from several papers.

**References**

1. Bauer and Rudebusch (2017). "Resolving the Spanning Puzzle in Macro-Finance Term Structure Models" (Review of Finance)
2. Candelon and Moura (2023). "Sovereign yield curves and the COVID-19 in emerging markets" (Economic Modelling)
3. Candelon and Moura (2024). "A Multicountry Model of the Term Structures of Interest Rates with a GVAR" (Journal of Financial Econometrics)

**Examples**

```
# Example 1:
LoadData("BR_2017")

# Example 2:
LoadData("CM_2023")

# Example 3:
LoadData("CM_2024")
```

Load\_Excel\_Data

*Read data from Excel files and return a named list of data frames***Description**

Read data from Excel files and return a named list of data frames

**Usage**

```
Load_Excel_Data(ExcelFilePath)
```

**Arguments**

**ExcelFilePath** character. Path to the Excel file (.xlsx) to load. Must be a valid file path. The file can contain multiple sheets; each sheet will be loaded as a separate data frame in the output list.

**Details**

Uses the readxl package to read all sheets from the specified Excel file. Each sheet is returned as a data frame. The output is a named list, with names matching the sheet names in the Excel file.

**Value**

Named list of data frames, one for each sheet in the Excel file. The names of the list elements correspond to the sheet names.

**Examples**

```
if (!requireNamespace("readxl", quietly = TRUE)) {
  stop(
    "Please install package \"readxl\" to use this feature.",
    call. = FALSE
  )

  Load_Excel_Data(system.file("extdata", "MacroData.xlsx", package = "MultiATSM"))
  Load_Excel_Data(system.file("extdata", "YieldsData.xlsx", package = "MultiATSM"))
}
```

MultiATSM

*ATSM Package***Description**

Estimation of several classes of affine term structure of interest rates models.

**Author(s)**

Rubens Moura <rubens.gtmoura@gmail.com>

MultiATSM\_datasets

*Overview of Datasets Included in the MultiATSM Package***Description**

The package includes several pre-processed datasets used for estimation and replication examples:

**Details**

**GlobalMacro** Global macro-financial risk factors, namely global economic activity and global inflation.

**GlobalMacro\_covid** Global macro-financial risk factors, namely the output growth rate from the U.S. and China and the S&P 500 index.

**DomMacro** Domestic macroeconomic risk factors, namely economic activity and inflation.

**DomMacro\_covid** Domestic macroeconomic risk factors, namely output growth, inflation, CDS and the COVID-19 reproduction rate

**TradeFlows** Bilateral trade flow series used in GVAR examples as a proxy measure of cross-country connectedness.

**TradeFlows\_covid** Bilateral trade flow series used in GVAR examples as a proxy measure of cross-country connectedness.

**Yields** Monthly series of bond yields by maturity for multiple economies.

**Yields\_covid** Weekly series of sovereign bond yields by maturity for multiple economies.

**RiskFacFull** Full set of risk factors (global and domestic) data used throughout the package

**GVARFactors** List of risk factors used in the estimation of GVAR models.

**BR\_jps\_out** Replications of the JPS outputs by Bauer and Rudebusch (2017)

**InpForOutEx** List of inputs for an illustrative JPS model with Brazilian data

**ParaSetEx** List of set of parameters after optimization for an illustrative JPS model with Brazilian data

**NumOutEx** List of numerical outputs for an illustrative JPS model with Brazilian data

**Out\_Example** re-loaded examaple of a complete list of several model outputs. Used in the package vignette.

Each dataset is documented separately using ‘?GlobalMacro’, ‘?DomMacro’, ‘?TradeFlows’, ‘?Yields’, etc. Datasets ending with the suffix `_covid` are based on those used in Candelon and Moura (2023) and cover Brazil, India, Mexico, and Russia. The remaining datasets correspond to Candelon and Moura (2024) and include Brazil, China, Mexico, and Uruguay.

References

1. Candelon, B. and Moura, R. (2023) "Sovereign yield curves and the COVID-19 in emerging markets". (Economic Modelling)

2. Candelon, B. and Moura, R. (2024) "A Multicountry Model of the Term Structures of Interest Rates with a GVAR". (Journal of Financial Econometrics)

|          |                                              |
|----------|----------------------------------------------|
| NumOutEx | <i>Example of computed numerical outputs</i> |
|----------|----------------------------------------------|

Description

Numerical outputs for JPS-based model using Brazilian data

Usage

```
data("NumOutEx")
```

Format

- list of inputs and outputs
- PC var explained** variance explained per spanned factor
- Fit** model fit of bond yields
- IRF** Impulse response function
- FEVD** Forecast error variance decomposition
- GIRF** Generalized impulse response function
- GFEVD** Generalized Forecast error variance decomposition
- TermPremiaDecomp** Term Premia decomposition

---

|            |                                                                                                        |
|------------|--------------------------------------------------------------------------------------------------------|
| NumOutputs | <i>Constructs the model numerical outputs (model fit, IRFs, GIRFs, FEVDs, GFEVDs, and term premia)</i> |
|------------|--------------------------------------------------------------------------------------------------------|

---

## Description

Constructs the model numerical outputs (model fit, IRFs, GIRFs, FEVDs, GFEVDs, and term premia)

## Usage

```
NumOutputs(
  ModelType,
  ModelPara,
  InputsForOutputs,
  FactorLabels,
  Economies,
  Folder2save = NULL,
  verbose = TRUE
)
```

## Arguments

|                  |                                                                                                                                                                                          |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ModelType        | character. Model type to be estimated. Permissible choices: "JPS original", "JPS global", "GVAR single", "JPS multi", "GVAR multi", "JLL original", "JLL No DomUnit", "JLL joint Sigma". |
| ModelPara        | list. Point estimates of the model parameters. See outputs from <a href="#">Optimization</a>                                                                                             |
| InputsForOutputs | list. Inputs for generating IRFs, GIRFs, FEVDs, GFEVDs, and Term Premia.                                                                                                                 |
| FactorLabels     | list. Labels for all variables present in the model, as returned by <a href="#">LabFac</a> .                                                                                             |
| Economies        | character vector. Names of the C economies included in the system.                                                                                                                       |
| Folder2save      | Folder path where the outputs will be stored. Default option saves the outputs in a temporary directory.                                                                                 |
| verbose          | Logical flag controlling function messaging. Default is TRUE.                                                                                                                            |

## Details

Both IRFs and FEVDs are computed using the Cholesky decomposition method. The risk factors are ordered as follows: (i) global unspanned factors, and (ii) domestic unspanned and spanned factors for each country. The order of countries follows the sequence defined in the Economies vector.

**Value**

An object of class 'ATSMNumOutputs' containing the following keys elements:

1. Model parameter estimates
2. Model fit of bond yields
3. IRFs
4. FEVDs
5. GIRFs
6. GFEVDs
7. Bond yield decomposition

**Available methods**

- 'autoplot(object, type)'

**References**

Pesaran, H. Hashem, and Shin, Yongcheol. "Generalized impulse response analysis in linear multi-variate models." *Economics letters* 58.1 (1998): 17-29.

**Examples**

```
data("ParaSetEx")
data("InpForOutEx")
# Adjust inputs according to the loaded features
ModelType <- "JPS original"
Economy <- "Brazil"
FacLab <- LabFac(N = 1, DomVar = "Eco_Act", GlobalVar = "G1_Eco_Act", Economy, ModelType)

NumOut <- NumOutputs(ModelType, ParaSetEx, InpForOutEx, FacLab, Economy,
  Folder2save = NULL, verbose = FALSE
)
```

---

Optimization

*Perform the optimization of the log-likelihood function of the chosen ATSM*

---

**Description**

Perform the optimization of the log-likelihood function of the chosen ATSM

**Usage**

```
Optimization(
  MLEinputs,
  StatQ,
  DataFreq,
  FactorLabels,
  Economies,
  ModelType,
  tol = 1e-04,
  EstType = c("BFGS", "Nelder-Mead"),
  TimeCount = TRUE,
  BS_outputs = FALSE,
  verbose = TRUE
)
```

**Arguments**

|              |                                                                                                                                                                                          |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MLEinputs    | list. Contains the inputs for building the log-likelihood function (see <a href="#">InputsForOpt</a> ).                                                                                  |
| StatQ        | A logical value indicating whether to impose that the largest eigenvalue under Q is strictly smaller than 1. Set TRUE to impose this restriction.                                        |
| DataFreq     | character vector specifying the data frequency. Available options: "Daily All Days", "Daily Business Days", "Weekly", "Monthly", "Quarterly", "Annually".                                |
| FactorLabels | list. Labels for all variables present in the model, as returned by <a href="#">LabFac</a> .                                                                                             |
| Economies    | character vector. Names of the C economies included in the system.                                                                                                                       |
| ModelType    | character. Model type to be estimated. Permissible choices: "JPS original", "JPS global", "GVAR single", "JPS multi", "GVAR multi", "JLL original", "JLL No DomUnit", "JLL joint Sigma". |
| tol          | numeric. Convergence tolerance. The default is 1e-4.                                                                                                                                     |
| EstType      | Available options are "BFGS" and/or "Nelder-Mead".                                                                                                                                       |
| TimeCount    | Logical. If TRUE, computes the time required for model estimation. Default is TRUE.                                                                                                      |
| BS_outputs   | Logical. If TRUE, generates a simplified output list in the bootstrap setting. Default is FALSE.                                                                                         |
| verbose      | Logical flag controlling function messaging. Default is TRUE.                                                                                                                            |

**Value**

An object of class 'ATSMModelOutputs' containing model outputs after the optimization of the chosen ATSM specification.

**Available Methods**

- 'summary(object)'

## References

- Candelon, C. and Moura, R. (2024). “A Multicountry Model of the Term Structures of Interest Rates with a GVAR.” *Journal of Financial Econometrics* 22 (5): 1558–87.
- Jotikasthira, C; Le, A. and Lundblad, C (2015). “Why Do Term Structures in Different Currencies Co-Move?” *Journal of Financial Economics* 115: 58–83.
- Joslin, S.; Pribsch, M. and Singleton, K. (2014). “Risk Premiums in Dynamic Term Structure Models with Unspanned Macro Risks.” *Journal of Finance* 69 (3): 1197–1233.
- Joslin, S., Singleton, K. and Zhu, H. (2011). "A new perspective on Gaussian dynamic term structure models". *The Review of Financial Studies*.
- Le, A. and Singleton, K. (2018). "A Small Package of Matlab Routines for the Estimation of Some Term Structure Models." Euro Area Business Cycle Network Training School - Term Structure Modelling.

## Examples

```
LoadData("CM_2024")
ModelType <- "JPS original"
Economy <- "Brazil"
t0 <- "01-05-2007" # Initial Sample Date (Format: "dd-mm-yyyy")
tF <- "01-12-2018" # Final Sample Date (Format: "dd-mm-yyyy")
N <- 1
GlobalVar <- "G1_Eco_Act" # Global Variables
DomVar <- "Eco_Act" # Domestic Variables
DataFreq <- "Monthly"
StatQ <- FALSE

FacLab <- LabFac(N, DomVar, GlobalVar, Economy, ModelType)
ATSMInputs <- InputsForOpt(t0, tF, ModelType, Yields, GlobalMacro, DomMacro,
  FacLab, Economy, DataFreq,
  CheckInputs = FALSE, verbose = FALSE
)

OptPara <- Optimization(ATSMInputs, StatQ, DataFreq, FacLab, Economy, ModelType, verbose = FALSE)
```

---

Out\_Example

*Complete list of several outputs from an ATSM*

---

## Description

Example for illustration used in the package vignette

## Usage

```
data("Out_Example")
```

**Format**

several model classes

**ModelParaList** List of parameter estimates of the selected ATSM

**ATSMinputs** General inputs from an ATSM

**Forecasts** List of forecast outputs

**NumOut** List of numerical outputs

**Bootstrap** List of set of outputs after bootstrap

---

 ParaSetEx

*Example of parameter set after optimization*


---

**Description**

JPS-based model for Brazilian data

**Usage**

```
data("ParaSetEx")
```

**Format**

list of inputs and outputs

**Inupts** general model inputs

**ModEst** model parameters estimates (JPS form)

---

 pca\_weights\_one\_country

*Computes the PCA weights for a single country*


---

**Description**

Computes the PCA weights for a single country

**Usage**

```
pca_weights_one_country(Yields, Economy)
```

**Arguments**

**Yields** matrix (J x Td). Bond yields for a single country.

**Economy** character. Name of the economy.

**Value**

matrix (J x J). Eigenvectors of the variance-covariance matrix of yields.

**General Notation**

- Td: model time series dimension
- J: number of bond yields per country used in estimation

**Examples**

```
data(Yields)
Economy <- "Mexico"
pca_weights <- pca_weights_one_country(Yields, Economy)
```

---

```
plot.ATSMModelForecast
```

*Plot method for ATSMModelForecast objects*

---

**Description**

Plot method for ATSMModelForecast objects

**Usage**

```
## S3 method for class 'ATSMModelForecast'
plot(x, ...)
```

**Arguments**

|     |                                      |
|-----|--------------------------------------|
| x   | An object of class ATSMModelForecast |
| ... | Additional arguments (not used)      |

---

```
print.ATSMModelInputs
```

*Print method for ATSMModelInputs objects*

---

**Description**

Print method for ATSMModelInputs objects

**Usage**

```
## S3 method for class 'ATSMModelInputs'
print(x, ...)
```

Arguments

- x                    An object of class 'ATSMModelInputs'
- ...                Additional arguments (not used)

---

|             |                                                                         |
|-------------|-------------------------------------------------------------------------|
| RiskFacFull | <i>Data: Full set of risk factors - Candelon and Moura (2024, JFEC)</i> |
|-------------|-------------------------------------------------------------------------|

---

Description

Full set of risk factors data used in Candelon and Moura (2024, JFEC)

Usage

```
data("RiskFacFull")
```

Format

matrix containing the full risk factors: (i) global unspanned factors (global economic activity and global inflation); (ii) domestic unspanned factors (economic activity and inflation); and (iii) domestic spanned factors (level, slope, and curvature). Economic system is formed by Brazil, China, Mexico and Uruguay. The data have monthly frequency and span the period from June/2004 to January/2020.

Source

- Global unspanned factor** See data("GlobalMacro") for a detailed data description.
- Domestic unspanned factor** See data("DomMacro") for a detailed data description.
- Domestic spanned factor** First three principal components of each country set of bond yields. See data("Yields") for a detailed data description.

References

Candelon, B. and Moura, R. (2024) "A Multicountry Model of the Term Structures of Interest Rates with a GVAR". (Journal of Financial Econometrics)

---

|                   |                                           |
|-------------------|-------------------------------------------|
| RiskFactorsGraphs | <i>Spanned and unspanned factors plot</i> |
|-------------------|-------------------------------------------|

---

### Description

Spanned and unspanned factors plot

### Usage

```
RiskFactorsGraphs(
  ModelType,
  WishRFgraphs,
  ModelOutputs,
  Economies,
  FactorLabels,
  Folder2save,
  verbose
)
```

### Arguments

|              |                                                                                                                                                                                    |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ModelType    | character. Estimated model type. Permissible choices: "JPS original", "JPS global", "GVAR single", "JPS multi", "GVAR multi", "JLL original", "JLL No DomUnit", "JLL joint Sigma". |
| WishRFgraphs | logical. Set TRUE to generate graphs, FALSE otherwise.                                                                                                                             |
| ModelOutputs | list. Model parameter estimates (see <a href="#">Optimization</a> ).                                                                                                               |
| Economies    | character vector. Names of the C economies included in the system.                                                                                                                 |
| FactorLabels | list. Labels for all variables in the model.                                                                                                                                       |
| Folder2save  | character. Folder path where the outputs will be stored.                                                                                                                           |
| verbose      | logical. Flag controlling function messaging.                                                                                                                                      |

### Available Methods

- 'autoplot(object, type = "RiskFactors")'

### Examples

```
data("ParaSetEx")
# Adapt factor labels according to the example
ModelType <- "JPS original"
Economy <- "Brazil"
FacLab <- LabFac(N = 1, DomVar = "Eco_Act", GlobalVar = "Gl_Eco_Act", Economy, ModelType)

RiskFactorsGraphs(ModelType,
  WishRFgraphs = FALSE, ParaSetEx, Economy, FacLab,
  Folder2save = NULL, verbose = FALSE
)
```

---

|                 |                                                      |
|-----------------|------------------------------------------------------|
| Spanned_Factors | <i>Computes the country-specific spanned factors</i> |
|-----------------|------------------------------------------------------|

---

**Description**

Computes the country-specific spanned factors

**Usage**

```
Spanned_Factors(Yields, Economies, N)
```

**Arguments**

|           |                                                                                            |
|-----------|--------------------------------------------------------------------------------------------|
| Yields    | matrix ( $J \times T_d$ ). Bond yields for all countries.                                  |
| Economies | character vector. Names of the $C$ economies included in the system.                       |
| N         | integer. Desired number of country-specific spanned factors (maximum allowed is $N = J$ ). |

**Value**

matrix. Contains the  $N$  spanned factors for all countries in the system ( $CJ \times T_d$ ).

**General Notation**

- $T_d$ : model time series dimension
- $C$ : number of countries in the system
- $N$ : number of country-specific spanned factors
- $J$ : number of bond yields per country used in estimation

**Examples**

```
data(Yields)
Economies <- c("China", "Brazil", "Mexico", "Uruguay")
N <- 3
SpaFact_TS <- Spanned_Factors(Yields, Economies, N)
```

---

summary.ATSMMModelInputs

*Summary method for ATSMModelInputs objects*

---

### Description

Summary method for ATSMModelInputs objects

### Usage

```
## S3 method for class 'ATSMMModelInputs'
summary(object, ...)
```

### Arguments

|        |                                       |
|--------|---------------------------------------|
| object | An object of class 'ATSMMModelInputs' |
| ...    | Additional arguments (not used)       |

---

summary.ATSMMModelOutputs

*Summary method for ATSMModelOutputs objects*

---

### Description

Summary method for ATSMModelOutputs objects

### Usage

```
## S3 method for class 'ATSMMModelOutputs'
summary(object, ...)
```

### Arguments

|        |                                        |
|--------|----------------------------------------|
| object | An object of class 'ATSMMModelOutputs' |
| ...    | Additional arguments (not used)        |

---

TPDecompGraph

*Term Premia decomposition graphs for all models*


---

## Description

Term Premia decomposition graphs for all models

## Usage

```
TPDecompGraph(
  ModelType,
  NumOut,
  ModelPara,
  WishRPgraphs,
  UnitYields,
  Economies,
  PathsGraphs,
  Folder2Save,
  verbose
)
```

## Arguments

|              |                                                                                                                                                                                    |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ModelType    | character. Estimated model type. Permissible choices: "JPS original", "JPS global", "GVAR single", "JPS multi", "GVAR multi", "JLL original", "JLL No DomUnit", "JLL joint Sigma". |
| NumOut       | list. Computed outputs containing model fit, IRFs, FEVDs, GIRFs, GFEVDs and risk premia.                                                                                           |
| ModelPara    | list. Model parameter estimates (see <a href="#">Optimization</a> ).                                                                                                               |
| WishRPgraphs | logical. Set TRUE to generate term premia graphs, FALSE otherwise.                                                                                                                 |
| UnitYields   | character. "Month" if yields are in months, "Year" if in years.                                                                                                                    |
| Economies    | character vector. Names of the C economies included in the system.                                                                                                                 |
| PathsGraphs  | character. Path of the folder in which the graphs will be saved.                                                                                                                   |
| Folder2Save  | character. Folder path where the outputs will be stored.                                                                                                                           |
| verbose      | logical. Flag controlling function messaging.                                                                                                                                      |

## Available Methods

- 'autoplot(object, type = "TermPremia")'

Examples

```
data("ParaSetEx")
data("NumOutEx")
ModelType <- "JPS original"
Economy <- "Brazil"
UnitYields <- "Month"
TPDecompGraph(ModelType, NumOutEx, ParaSetEx,
  WishRPgraphs = FALSE, UnitYields, Economy,
  PathsGraphs = NULL, Folder2Save = NULL, verbose = FALSE
)
```

---

|            |                                                            |
|------------|------------------------------------------------------------|
| TradeFlows | <i>Data: Trade Flows - Candelon and Moura (2024, JFEC)</i> |
|------------|------------------------------------------------------------|

---

Description

Trade Flows data used in Candelon and Moura (2024, JFEC)

Usage

```
data("TradeFlows")
```

Format

A list. Contains bilateral trade flow data for Brazil, China, Mexico, and Uruguay, covering the sample period from 1948 to 2019.

Source

International Monetary Fund - International Trade in Goods (IMTS) <<https://data.imf.org/en/datasets/IMF.STA:IMTS>>

References

Candelon, B. and Moura, R. (2024) "A Multicountry Model of the Term Structures of Interest Rates with a GVAR". (Journal of Financial Econometrics)

---

|                  |                                                          |
|------------------|----------------------------------------------------------|
| TradeFlows_covid | <i>Data: Trade Flows - Candelon and Moura (2023, EM)</i> |
|------------------|----------------------------------------------------------|

---

**Description**

Trade Flows data used in Candelon and Moura (2023, EM)

**Usage**

```
data("TradeFlows_covid")
```

**Format**

A list. Contains bilateral trade flow data for Brazil, India, Mexico, and Russia, covering the sample period from 1948 to 2020.

**Source**

International Monetary Fund - International Trade in Goods (IMTS) <<https://data.imf.org/en/datasets/IMF.STA:IMTS>>

**References**

Candelon, B. and Moura, R. (2023) "Sovereign yield curves and the COVID-19 in emerging markets". (Economic Modelling)

---

|                   |                                                                                    |
|-------------------|------------------------------------------------------------------------------------|
| Transition_Matrix | <i>Computes the transition matrix required in the estimation of the GVAR model</i> |
|-------------------|------------------------------------------------------------------------------------|

---

**Description**

Computes the transition matrix required in the estimation of the GVAR model

**Usage**

```
Transition_Matrix(t_First, t_Last, Economies, type, DataConnectedness)
```

**Arguments**

|           |                                                                                                                                                                                                                       |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| t_First   | character. Sample starting date (format: yyyy).                                                                                                                                                                       |
| t_Last    | character. Sample ending date (format: yyyy).                                                                                                                                                                         |
| Economies | character vector. Names of the C economies included in the system.                                                                                                                                                    |
| type      | character. Method for computing interdependence. Possible options: <ul style="list-style-type: none"> <li>"Time-varying": Computes time-varying interdependence and returns weight matrices for each year.</li> </ul> |

- "Sample Mean": Returns a single weight matrix with average weights over the sample period.
- Specific year (e.g., "1998", "2005"): Computes time-invariant interdependence for the specified year.

DataConnectedness

list or data frame. Data used to compute the transition matrix (e.g., trade flows).

## Details

If there is missing data for any country in a particular year, the transition matrix will include only NAs.

## Value

matrix or list of matrices. Time-varying or time-invariant transition matrix depending on 'type'.

## Examples

```
t_First <- "2006"
t_Last <- "2019"
Economies <- c("China", "Brazil", "Mexico", "Uruguay")
type <- "Sample Mean"
# Load data if Connectedness data from excel, otherwise use pre-saved data
GetExcelData <- FALSE

if (GetExcelData) {
  if (!requireNamespace("readxl", quietly = TRUE)) {
    stop(
      "Please install package \"readxl\" to use this feature.",
      call. = FALSE
    )
    DataPath <- system.file("extdata", "TradeData.xlsx", package = "MultiATSM")
    tab_names_Trade <- readxl::excel_sheets(DataPath)
    list_all_Trade <- suppressMessages(lapply(tab_names_Trade, function(x) {
      readxl::read_excel(path = DataPath, sheet = x)
    }))
    names(list_all_Trade) <- tab_names_Trade

    L <- length(list_all_Trade)

    for (i in 1:L) {
      Countries <- list_all_Trade[[i]][[1]]
      list_all_Trade[[i]] <- as.data.frame(list_all_Trade[[i]][, -1])
      rownames(list_all_Trade[[i]]) <- Countries
    }

    DataConnectedness <- list_all_Trade
  }
} else {
  data(TradeFlows)
  DataConnectedness <- TradeFlows
}
```

```
W_mat <- Transition_Matrix(t_First, t_Last, Economies, type, DataConnectedness)
```

---

VAR

*Estimates a standard VAR(1)*


---

## Description

Estimates a standard VAR(1)

## Usage

```
VAR(RiskFactors, VARtype, Bcon_Mat = NULL)
```

## Arguments

|             |                                                                                                                                               |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| RiskFactors | numeric matrix ( $K \times T_d$ ). Time series of risk factors.                                                                               |
| VARtype     | character. Permissible choices: "unconstrained" or "constrained".                                                                             |
| Bcon_Mat    | matrix ( $K \times K + 1$ ). Constraints matrix (includes intercept). Entries containing NAs are treated as free parameters. Default is NULL. |

## Value

list. Contains:

- intercept ( $K \times 1$ )
- feedback matrix ( $K \times K$ )
- variance-covariance matrix ( $K \times K$ ) of a VAR(1)

## General Notation

- $T_d$ : model time series dimension
- $N$ : number of country-specific spanned factors
- $K$ : total number of risk factors

## Examples

```
data(RiskFacFull)
# Example 1: unconstrained case
VAR_para1 <- VAR(RiskFacFull, VARtype = "unconstrained")

# Example 2: constrained case
K <- nrow(RiskFacFull)
Bcon_Mat <- matrix(0, nrow = K, ncol = K + 1)
Bcon_Mat[, 1:3] <- NaN
VAR_para2 <- VAR(RiskFacFull, VARtype = "constrained", Bcon_Mat)
```

---

|        |                                                                |
|--------|----------------------------------------------------------------|
| Yields | <i>Data: bond yield data - Candelon and Moura (2024, JFEC)</i> |
|--------|----------------------------------------------------------------|

---

**Description**

Yields data used in Candelon and Moura (2024, JFEC)

**Usage**

```
data("Yields")
```

**Format**

A matrix containing bond yields with maturities of 3, 6, 12, 36, 60, and 120 months for Brazil, China, Mexico, and Uruguay. The data are at monthly frequency and cover the period from June 2004, to January 2020.

**Source**

- Brazil** Swap fixed-DI contracts (derivative securities indexed to the interbank loan rates). <[https://www.b3.com.br/pt\\_br/market-data-e-indices/servicos-de-dados/market-data/consultas/mercado-de-derivativos/precos-referenciais/taxas-referenciais-bm-fbovespa/](https://www.b3.com.br/pt_br/market-data-e-indices/servicos-de-dados/market-data/consultas/mercado-de-derivativos/precos-referenciais/taxas-referenciais-bm-fbovespa/)>
- China** Government bond yield data in domestic currency. Simulated data constructed using Bloomberg bond yield series.
- Mexico** Government bond yield data in domestic currency. Simulated data constructed using Bloomberg bond yield series.
- Uruguay** Government bond yield data in US dollars <<https://web.bevsa.com.uy/CurvasVectorPrecios/CurvasIndices/CUD.as>>

**References**

Candelon, B. and Moura, R. (2024) "A Multicountry Model of the Term Structures of Interest Rates with a GVAR". (Journal of Financial Econometrics)

---

|              |                                                 |
|--------------|-------------------------------------------------|
| Yields_covid | <i>Data: Yields - Candelon and Moura (2023)</i> |
|--------------|-------------------------------------------------|

---

**Description**

Bond yield data used in Candelon and Moura (2023)

**Usage**

```
data("Yields_covid")
```

**Format**

A matrix containing Government bond yields with maturities of 12, 24, 36, 60, and 120 months for Brazil, India, Mexico, and Russia. The data are at weekly frequency and cover the period from March 22, 2020, to September 26, 2021.

**Source**

Simulated data constructed using Bloomberg bond yield series.

**References**

Cadelon, B. and Moura, R. (2023) "Sovereign yield curves and the COVID-19 in emerging markets". (Economic Modelling)

# Index

- \* **Bond**
  - Yields, [50](#)
- \* **Brazilian**
  - ParaSetEx, [39](#)
- \* **Brazil**
  - InpForOutEx, [22](#)
  - NumOutEx, [34](#)
  - Out\_Example, [38](#)
- \* **Domestic**
  - DomMacro, [12](#)
- \* **Factors**
  - GVARFactors, [21](#)
  - RiskFacFull, [41](#)
- \* **Flows**
  - TradeFlows, [46](#)
  - TradeFlows\_covid, [47](#)
- \* **GVAR**
  - GVARFactors, [21](#)
- \* **Global**
  - GlobalMacro, [18](#)
  - GlobalMacro\_covid, [19](#)
- \* **Illustrative**
  - ParaSetEx, [39](#)
- \* **JPS**
  - InpForOutEx, [22](#)
  - NumOutEx, [34](#)
  - Out\_Example, [38](#)
  - ParaSetEx, [39](#)
- \* **Numerical**
  - NumOutEx, [34](#)
  - Out\_Example, [38](#)
- \* **Risk**
  - GVARFactors, [21](#)
  - RiskFacFull, [41](#)
- \* **Trade**
  - TradeFlows, [46](#)
  - TradeFlows\_covid, [47](#)
- \* **Yields**
  - Yields\_covid, [50](#)
- \* **an**
  - InpForOutEx, [22](#)
  - NumOutEx, [34](#)
  - Out\_Example, [38](#)
- \* **data**
  - ParaSetEx, [39](#)
- \* **domestic**
  - DomMacro\_covid, [13](#)
- \* **factors**
  - DomMacro, [12](#)
  - DomMacro\_covid, [13](#)
  - GlobalMacro, [18](#)
  - GlobalMacro\_covid, [19](#)
- \* **for**
  - InpForOutEx, [22](#)
  - NumOutEx, [34](#)
  - Out\_Example, [38](#)
  - ParaSetEx, [39](#)
- \* **illustrative**
  - InpForOutEx, [22](#)
  - NumOutEx, [34](#)
  - Out\_Example, [38](#)
- \* **inputs**
  - InpForOutEx, [22](#)
- \* **list**
  - InpForOutEx, [22](#)
- \* **model**
  - InpForOutEx, [22](#)
  - NumOutEx, [34](#)
  - Out\_Example, [38](#)
  - ParaSetEx, [39](#)
- \* **of**
  - InpForOutEx, [22](#)
- \* **outputs**
  - BR\_jps\_out, [8](#)
  - NumOutEx, [34](#)
  - Out\_Example, [38](#)
- \* **replication**
  - BR\_jps\_out, [8](#)

- \* **risk**
  - DomMacro, [12](#)
  - DomMacro\_covid, [13](#)
  - GlobalMacro, [18](#)
  - GlobalMacro\_covid, [19](#)
- \* **unspanned**
  - DomMacro, [12](#)
- \* **yields**
  - Yields, [50](#)
- autoplot, [3](#)
- autoplot.ATSMModelBoot, [3](#)
- autoplot.ATSMNumOutputs, [4](#)
- Bias\_Correc\_VAR, [4](#), [7](#), [17](#), [23](#)
- Bootstrap, [6](#)
- BR\_jps\_out, [8](#)
- DatabasePrep, [9](#)
- DataForEstimation, [10](#)
- DomMacro, [12](#)
- DomMacro\_covid, [13](#)
- FEVDandGFEVDgraphs, [14](#)
- Fitgraphs, [15](#)
- ForecastYields, [16](#)
- GlobalMacro, [18](#)
- GlobalMacro\_covid, [19](#)
- GVAR, [5](#), [7](#), [17](#), [19](#)
- GVARFactors, [21](#)
- InpForOutEx, [22](#)
- InputsForOpt, [22](#), [37](#)
- InputsForOutputs, [26](#)
- IRFandGIRFgraphs, [28](#)
- JLL, [5](#), [7](#), [17](#), [29](#)
- LabFac, [7](#), [9](#), [11](#), [17](#), [23](#), [30](#), [35](#), [37](#)
- Load\_Excel\_Data, [9](#), [12](#), [32](#)
- LoadData, [31](#)
- MultiATSM, [33](#)
- MultiATSM-package (MultiATSM), [33](#)
- MultiATSM\_datasets, [33](#)
- NumOutEx, [34](#)
- NumOutputs, [7](#), [35](#)
- Optimization, [7](#), [15](#), [17](#), [35](#), [36](#), [42](#), [45](#)
- Out\_Example, [38](#)
- ParaSetEx, [39](#)
- pca\_weights\_one\_country, [39](#)
- plot.ATSMModelForecast, [40](#)
- print.ATSMModelInputs, [40](#)
- RiskFacFull, [41](#)
- RiskFactorsGraphs, [42](#)
- Spanned\_Factors, [43](#)
- summary.ATSMModelInputs, [44](#)
- summary.ATSMModelOutputs, [44](#)
- TPDecompGraph, [45](#)
- TradeFlows, [46](#)
- TradeFlows\_covid, [47](#)
- Transition\_Matrix, [20](#), [22](#), [47](#)
- VAR, [49](#)
- Yields, [50](#)
- Yields\_covid, [50](#)